



型式 TYPE	伝熱面積 HEAT TRANSFER AREA	A	B	C	Dφ	E	F	N-Hφ	H	重量 WEIGHT
HCR-KT-40	0.25 m ²	1000	900	50	48.6	40A	20A	4-19	49	5.5 kg
HCR-KT-50	0.47	1000	890	55	60.5	50A	25A	4-19	59	7.0
HCR-KT-65	0.90	1000	880	60	76.3	65A	32A	4-19	70	11.0
HCR-KT-80	1.38	1000	870	65	89.1	80A	40A	8-19	78	13.0
HCR-KT-100	2.20	1000	860	70	114.3	100A	50A	8-19	95	17.0
HCR-KT-125	3.50	1000	860	70	139.8	125A	50A	8-23	110	24.0
HCR-KT-150	5.00	1000	830	85	165.2	150A	65A	8-23	127	32.0
HCR-KT-200	8.80	1000	800	100	216.3	200A	80A	12-23	150	67.0

5	ノズルソケット NOZZLE SOCKET	SUS304	2	PT
4	バッフル BAFFLE	SUS304	5	
3	チューブ TUBE	TITAN		8.0 ^φ x0.4 ^t
2	シェル SHELL	SUS304	1	
1	ノズルフランジ NOZZLE FLANGE	SUS329J4L	2	
品番 ITEM	部品名称 NAME	材質 MATERIALS	数量 QTY	備考 REMARKS

HCR-KT

図面番号
DRAWING No.
REFERENCE DRAWING

ゼンシン 株式会社
ZENSHIN CO.,LTD
JAPAN